


## Stainless Steel Liquid Tight Conduit ( YF-706-SS )



Stainless Steel Liquid Tight Conduit



- \*Liquid-tight
- \*High tensile strength
- \*Stainless steel construction for increased corrosion resistance

Type <i>Stainless Steel</i>	Trade Size	I.D. (mm)		O.D. (mm)		Min. Bending Radius (mm)	Meters/Coil
		MIN.	MAX.	MIN.	MAX.		
YF-70603-SS	3/8"	12.5	13.0	17.8	18.3	60	50
YF-70604-SS	1/2"	16.1	16.6	21.3	21.8	80	50
YF-70606-SS	3/4"	20.7	21.3	25.9	26.4	100	30
YF-70610-SS	1"	26.3	26.8	33.3	33.8	150	30
YF-70612-SS	1-1/4"	35.0	35.5	42.6	43.1	180	20
YF-70614-SS	1-1/2"	40.0	40.5	47.6	48.0	220	20
YF-70620-SS	2"	51.0	51.5	60.3	60.8	250	15
YF-70624-SS	2-1/2"	63.0	63.7	72.2	73.0	300	10
YF-70630-SS	3"	78.0	78.8	88.2	89.0	450	10
YF-70640-SS	4"	101.8	102.8	113.2	114.0	600	5

Stainless steel liquid tight conduit and liquid tight connector is most suitable for *corrosion environments* applications, including Food & beverage, Petrochem plants, Wastewater treatment, Pulp & paper mills, Offshore applications, and Mining Industry